



CHECKMASTER INDICATOR SPECIFICATION SHEET

The CheckMaster indicator is designed for seamless integration with a MARCO weighing workstation, connecting to an individual weighing platform within the MARCO Trac-IT Yield Control System. Engineered to streamline operations, the CheckMaster simplifies decision-making for operators, ensuring a more efficient and accurate weighing process.

The indicator has been designed to operate in a high care working environment and requires a 110-240V power supply.

PRODUCT SPECIFICATION

Width:	282mm
Height:	160mm
Depth:	60mm
Material:	304 Stainless Steel
IP Rating:	IP69
Touch Screen:	W024064A1-TFH, 240x64 COG FSTN positive LCD with integrated touch panel
Delta-Sigma type:	Analog-Digital Converter
Internal resolution:	1: 1,000,000
Display resolution:	1: 500,000 (x10 Test Mode, non-trade use)

Weighing performance optimised for best speed and stability
Bright 16 Section LED Light bar guide for filling/check weighing
RS232 Serial or Wi-Fi Enabled communications

-10 to +40°C Operating Temperature Range

Universal power supply 90-260Vac 50-60Hz

Battery backed Real Time Clock/Calendar

Extensive features to operate stand alone or compliment the MARCO range of system software.

- NAWI Approved for USA
- 4 Digit PIN Log In
- Low Voltage Directive: 2014/35/EU
- Wi-Fi
- EMC Directive: 2014/30/EU

CHECKMASTER INDICATOR SPECIFICATION SHEET

