



CPI INDICATOR SPECIFICATION SHEET

PRODUCT SPECIFICATION

Width: 144mm
Height: 72mm
Depth: 63mm
Weight: 0.34kg

Annunciators: 4 LEDS (Motion/Zero/Net/Gross)
Front Panel: Membrane with tactile metal domes, Beep response, 5 button operation
Internal resolution: 24 bit ADC (1:16,777,215)
Display: 7 Red LED digits 14mm
Input Signal Range: -6.5 → 6.5 mV/V
Operating Voltage: 12-28VdC
Power Consumption: 5 - 10W
Maximum Display Resolution (trade): 10,000 (trade) | 500,000 (x 10 test mode) (non trade)
Zero Offset Range: 100% of Input Signal Range
ADC Conversion Rate(Hz): 50 (25/100*)
Linearity error (%FS): < ± 0.0015% (+ digital correction)
Differential non linearity: ± 0.5 LSB
Span temperature coefficient: 1.6 ppm/°C
Zero temperature coefficient: < 0.005 µV/oC
Common Mode Rejection (@500Hz): 120dB
Power Supply Rejection (@500Hz): 120dB
EC Approvals OIML Class III + IIII s: Certificate: UK: UK3180, EU: 0200-NAWI-08407

OPTIONS

15 bit Analogue Output 4-20mA or 0-10V
Flash Electronic Tally Record (Alibi device)
ModBus Communications

KEY FEATURES

- Bright, easy to read, large LED display
- DIN Standard, panel mount enclosure
- Two part connectors for quick replacement
- Multi point linearity adjustment
- Configuration via front panel or serial communication
- Two serial ports, printer port can be used for remote display
- Memory tares, semi automatic tare and set zero functions
- 3 outputs, 2 inputs as standard
- Trade Approved for any R60 loadcells
- Screwless, Push-In Spring
- Real time clock as standard
- Versatile print formatting
- PLU's recalling A/N text, set points, part weights and totals
- Multi-drop communications
- Sophisticated fill control with fast cut off and predictive software
- Variety of set point operating modes.
- Accommodates extremes of dead load and signal
- Superb digital weight filtering with fast settle times
- x10 resolution test mode
- Firmware upgrades via serial port

CPI INDICATOR SPECIFICATION SHEET



ENVIRONMENT:

IP Rating:	IP54
Operating Temperature Range:	-10 to +40°C
Storage Temperature Range:	-10 to +70°C
Enclosure:	Panel mount DIN Standard 43700
EMC Immunity/Emissions:	EN45501, EN50082-2

TRANSDUCER INPUT:

Transducer type (4 or 6 wire):	Resistive, full bridge
Transducer input resistance:	min 43Ω (up to 8 x 350Ω cells)
Excitation voltage:	5 (nominal) vDC
Minimum signal requirement:	1 μV/e (approved) 0.1 μV/e (non approved)
Input impedance:	≥ 20 (sense and signal) MΩ

SERIAL COMMUNICATION

Communication Ports:	1. Comms RS232 or RS485 2. Printer Port RS232 (TX/Busy)
Baud Rate:	2400, 4800, 9600, 19200, 38400 bits/sec
Protocol:	7/8 data bits, odd/even/no parity, 1/2 stop bits
Maximum continuous data rate:	50Hz (test mode)
Communication protocol:	Ascii or ModBus*

I/O

Analogue output* 0-10V or 4-20ma:	15 bit (adjustable range) Max drive load for 4-20mA: 500Ω (active)/1200Ω (passive)
Inputs 2 (4*):	Opto coupled inputs. <6V off; >10 -30V on (supply rail on board)
Outputs 3 (5*):	Darlington type transistors. Max OFF voltage 27V Max ON current 60mA. Leakage <0.1ma Switched + or -

* According to specification

