



LINEMASTER V INDICATOR SPECIFICATION SHEET

INDUSTRIES



READY TO EAT



CONVENIENCE FOOD



FRESH PRODUCE



FISH



MEAT/POULTRY

The LineMaster V indicator is designed for seamless integration with MARCO weighing workstations, connecting to an individual weighing platform within the MARCO Trac-IT Yield Control System.

Engineered for efficiency, the LineMaster V streamlines decision-making for operators, enhancing accuracy and productivity. This innovative solution simplifies complex tasks, ensuring precise control and optimised performance in every weighing process.

PRODUCT SPECIFICATION

Width: 376mm

Height: 218mm

Depth: 108mm

- NAWI Approved for UK/EU, USA, Canada, South Africa & Australia
- 4 Digit PIN Log In
- EMC Directive: 2014/30/EU
- Low Voltage Directive: 2014/35/EU
- Wi-Fi

Material: 304 Stainless Steel

IP Rating: IP69

Touch Screen: W024064A1-TFH, 240x64 COG FSTN positive LCD with integrated touch panel

Delta-Sigma type: Analog-Digital Converter

Internal resolution: 1: 1,000,000

Display resolution: 1: 500,000 (x10 Test Mode, non-trade use)

Weighing performance optimised for best speed and stability

Bright 16 Section LED Light bar guide for filling/check weighing

RS232 Serial or Wi-Fi Enabled communications

-10 to +40°C Operating Temperature Range

Universal power supply 90-260Vac 50-60Hz

Battery backed Real Time Clock/Calendar

Extensive features to operate stand alone or compliment the MARCO range of system software.

KEY FEATURES:

- Operator accountability via approved ID log In
- High Speed Portion Control
- Visual Lightbar Indicator
- Rated IP69 designed to operate in harsh environments
- Available in battery or mains powered
- Gesture Sensor (no touch tare)

BENEFITS:

- Minimise Giveaway
- Boost Productivity
- Increase Pack Accuracy
- Consistent Product Quality
- Complete Control & Traceability
- Reduce Waste
- Rapid ROI

LINEMASTER INDICATOR SPECIFICATION SHEET

